




Features

- Intel 13th Raptor Lake-P CPU i7-1365UE/i5-1335UE/i3-1315UE
- Supports DDR5 5200MHz, 2xSO-DIMM, up to 96GB system memory
- Triple display by 1 x HDMI, 1 x miniDP, 1 x USB3.2 Type-C,
- 3 x USB 3.2 Gen2 Type A, 6 x USB 2.0 Type A, 1 x USB 3.2 Type C
- 2 x Intel 2.5GbE LAN, 2 x COM, COM1/2 by RS-485/422/232
- Onboard M.2 B-Key, Nano SIM card slot, support TPM 2.0
- 1x M.2 2280 Gen4x4 for AI Acceleration Module
- 1x M.2 2242 Gen3x2 , 1 x M.2 2242/3042 B-Key for storage
- DC 9~36V input, option 60W(12V/5A) power adapter
- Supports Microsoft Windows 10/11 IoT 64bit LTSC

Specifications

AES-2120 Series Key Features		AES-2130P-M0M00P0	AES-2130M-M0M00P0	AES-2130V-M0M00P0
Processor System	CPU Max. Speed	Up 4.9GHz/1.7GHz	Up 4.5GHz/1.3GHz	Up 4.5GHz/1.2GHz
	L2 Cache/ Core/ Thread	12MB, 10-Core, 12-T	12MB, 10-Core, 12-T	10MB, 6-Core, 8-T
	CPU/ TDP	i7-1365UE/ 15W	i5-1335UE/ 15W	i3-1315UE, 15W
	BIOS	UEFI, AMI SPI 256Mbit		
	Graphics Processor	Intel UHD Graphics		
Security	TPM	TPM2.0		
Expansion Slot	M.2 B-Key	1 x M.2 B-Key 2242/3042 (PCIe x1/SATA 3.0/USB 2.0 and LTE module) Slot		
		1 x Nano SIM socket (connected to M.2 B key)		
	M.2 M-Key	1 x M.2 M-Key 2242(Gen3 PCIe x 2 NVMe)		
	M.2 E-Key	1 x M.2 E-Key 2230(PCIe x1/USB 2.0) for Wireless, on soldering side		
Memory	Specification (SO-DIMM)	2 x DDR5 5200MHz SO-DIMM		
	System Max. Capacity	96GB		
Graphics	HDMI/miniDP/Type-C	1 x HDMI 1.4, 1 x miniDP, 1 x USB Type-C		
Ethernet	LAN Gigabit Controller	2 x 2.5GbE LAN (Intel I226-LM)		
Storage	M.2 B/M-Key	1 x M.2 B-Key 2280 SATA 3.0, 1 x M.2 M-Key PCIe x1 NVMe		
	2.5" SATA Driver	1 x 2.5" SATA HDD/SSD (option)		
System Rear I/O	HDMI	1 x HDMI 1.4 (resolution up to 4K @ 24Hz)		
	MiniDP	1 x MiniDP (resolution up to 4K @ 30Hz)		
	USB Type C	1 x USB Type-C (USB 3.2 Gen2, DP1.4a, resolution up to 4K @ 60Hz)		
	USB Type A	3 x USB 3.2(Gen 2), 2 x USB 2.0		
	Ethernet	2 x 2.5GbE(RJ-45)		
	System Power Input	1 x DC-IN 9V~36V by 2-pin connector (+/-10% DC)		
	Audio	1 x Audio port (Line-out)		
System Front Bezel	Antenna	2 x Antenna holes (options)		
	Power-On Button	1 x Moment button switch to turn-on system		
	System Power LED	1 x LED for system power status		
	HDD LED	1 x LED for SSD data access status		
	COM1 / COM2 Port	2 x DB-9 (RS-232/422/485)		
	USB Type A	4 x USB 2.0		
Operation System	Windows 64-bit	Win 10/11 IoT 64-bit		
	Linux 64-bit	Ubuntu 19.04 / 20.04		
Watchdog Timer	Output and Interval	System reset, programmable 1 ~ 255 sec/min; 1 sec. or 1min. /step		
Power Requirement	DC Input	Wide Voltage 9~36Vdc input (option DC12V/5A 60W adapter)		
Environment	Operating Temperature	-40°C ~ 55°C(-40°F ~ 131°F)		
	Air Flow condition	55°C ~60°C (131°F ~140°F) w/0.5m/s air flow		
	Storage Temperature	-40 ~ 85°C (-40°F ~ 185°F)		
Physical Size	Dimensions	225mm(W) x 140mm(D) x 45mm(H)		
Packing Size	Dimensions	300mm(W) x 270mm(D) x 130mm(H)		
Weight	N.W / G.W.	Single packed: 2.5Kg / 3Kg		
Certifications	EMC			

Dimensions Outlook



Ordering Information

Part Number	CPU	DP/mDP/Type-C	2.5G LAN	USB 3.1	USB 2.0	COM	DDR5 RAM	M.2 M-Key(2242)	60W PSU
AES-2130P-M0M00P0	i7-1365UE	1/1/1	2	3/1	6	2	Option	Option	Option
AES-2130M-M0M00P0	i5-1335UE	1/1/1	2	3/1	6	2	Option	Option	Option
AES-2130V-M0M00P0	i3-1315UE	1/1/1	2	3/1	6	2	Option	Option	Option

Optional Items

Part Number	Description
SODIMM-DDR5	262-Pin SO-DIMM DDR5-5200 8GB
M2-P8A(2280)	M.2 2280 128GB Gen4x4 3D-TLC by M-KEY (on soldering side)
M2-P4A(2242)	M.2 2242 128GB Gen3x2 3D-TLC by M-KEY
M2-S4A(2242)	M.2 2242 128GB SATA3 3D-TLC by B-KEY
AC-9260	M.2 2230 (E-KEY) Wi-Fi Module, Intel AC9260 802.11abgn + Bluetooth 5.0, dual band 2T2R
DHAN3-60W-2P	AC-DC 60W Adapter, 90V-264Vac input by C14 socket, DC 12V@5A output with 2-pin phoneix connector
AES-WM-BK	AES Wall Mount Kits with Screws